

Please type a plus (+) inside this box → ☐

PTO/SB/29 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

8498-027-999

Total Pages

28

First Named Inventor or Application Identifier

JIMMY R. ROEHRIG

Express Mail Label No.

EL 066 225 485 US

U.S. PATENT
09/14/2009

08/27/98

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
Submit an original, and a duplicate for fee processing

2. ☒ Specification [Total Pages 20]

(preferred arrangement set forth below)

-Descriptive title of the Invention

-Cross Reference to Related Applications

-Statement Regarding Fed sponsored R&D

-Reference to Microfiche Appendix

-Background of the Invention

-Brief Summary of the Invention

-Brief Description of the Drawings (if filed)

-Detailed Description of the Invention (including drawings, if filed)

-Claim(s)

-Abstract of the Disclosure

3. ☒ Drawing(s) (35 USC 113) [Total Sheets 4]

4. ☒ Oath or Declaration unexecuted [Total Sheets 2]

a. ☐ Newly executed (original or copy)

b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]

i. ☐ DELETION OF INVENTOR(S)

Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33 (b).

5. ☐ Incorporation By Reference (useable if Box 4b is checked)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

a. ☐ Computer Readable Copy

b. ☐ Paper Copy (identical to computer copy)

c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))

9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)

10. ☐ English Translation Document (if applicable)

11. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

14. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired

15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)

16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) of prior application No: 09/103,290 filed June 23, 1998 which is a continuation of application no. 08/676,660 filed July 10, 1996, .

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

20583

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

NAME

ADDRESS

CITY

STATE

ZIP CODE

COUNTRY

TELEPHONE

FAX

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PENNIE & EDMONDS LLP

COUNSELLORS AT LAW
1155 Avenue of the Americas
New York, N.Y. 10036-2711
(212) 790-9090

ATTORNEY DOCKET NO. 8498-027-999Date August 27, 1998

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

The following utility patent application is enclosed for filing:

Applicants: Jimmy R. ROEHRIG, Takeshi DOI, Nico
KARSSEMEIJER, Guido M. te BRAKE

Executed on: Unexecuted


Title of Invention: METHOD AND SYSTEM FOR DETECTION OF SUSPICIOUS LESIONS IN DIGITAL
MAMMOGRAMS USING A COMBINATION OF SPICULATION AND DENSITY SIGNALS

PATENT APPLICATION FEE VALUE

TYPE	NO. FILED	LESS	EXTRA	EXTRA RATE	FEE
Total Claims	20	-20	0	\$22.00 each	0.00
Independent	3	-3	0	\$82.00 each	0.00
Minimum Fee					790.00
Multiple Dependency Fee If Applicable (\$270.00)					
Total					790.00
50% Reduction for Independent Inventor, Nonprofit Organization or Small Business Concern (a verified statement as to the applicant's status is attached)					- 395.00
Total Filing Fee					\$ 395.00

- ☒ Priority of application no. 09/103,290 filed on June 23, 1998 which is a continuation of U.S. Application No. 08/676,660 filed July 10, 1996 is claimed under 35 U.S.C. § 120.
- ☐ The certified copy of the priority application has been filed in application no. filed .
- ☐ Amend the specification by inserting before the first line the following sentence; This is a continuation-in-part of application no. filed .

Respectfully submitted,



Francis E. Morris

PENNIE & EDMONDS LLP

38,825 For: 24,615
(Reg. No.)

Enclosure

This form is not for use with continuation, divisional, re-issue, design or plant patent applications.

**METHOD AND SYSTEM FOR DETECTION OF
SUSPICIOUS LESIONS IN DIGITAL MAMMOGRAMS
USING A COMBINATION OF SPICULATION AND DENSITY SIGNALS**

Jimmy R. Roehrig
Takeshi Doi
Nico Karssemeijer
Guido M. te Brake

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S.
10 Patent Application Serial No. 09/103,290, entitled "Method
and Apparatus for Fast Detection of Spiculated Lesions in
Digital Mammograms," filed June 23, 1998, which is a
continuation of U.S. Patent Application Serial No.
08/676,660, filed July 10, 1996, for which a notice of
15 allowance was mailed on May 12, 1998 for which an issue fee
was paid on May 19, 1998. Both of the above applications are
assigned to the assignee of the present invention. The above
applications are hereby incorporated by reference into the
present application.

20

FIELD OF THE INVENTION

The present invention relates to the field of computer
aided diagnosis of medical images. In particular, the
invention relates to a method and apparatus for detecting
25 suspicious lesions in digital mammograms using an algorithm
that independently computes mass information and spiculation
information for allowing faster and more reliable
identification of suspicious lesions.

30

BACKGROUND OF THE INVENTION

Breast cancer in women is a serious health problem. The
American Cancer Society currently estimates that over 180,000
U.S. women are diagnosed with breast cancer each year.
Breast cancer is the second major cause of cancer death among
35 women. The American Cancer Society also estimates that
breast cancer causes the death of over 44,000 U.S. women each
year. While, at present, there is no means for preventing

breast cancer, early detection of the disease prolongs life expectancy and decreases the likelihood of the need for a total mastectomy. Mammography using x-rays is currently the most common method of detecting and analyzing breast tumors.

5 Detection of suspicious, i.e. possibly cancerous, areas in mammograms is an important first step in the early diagnosis and treatment of breast cancer. While it is important to detect suspicious lesions when they are in the early stages, practical considerations can make this
10 difficult. One complicating factor is that a typical mammogram may contain myriads of lines corresponding to fibrous breast tissue. The trained, focused eye of a medical professional, such as a radiologist, is needed to detect suspicious features among these lines. A typical radiologist
15 may be required to examine hundreds of mammograms per day, leading to the possibility of a missed diagnosis due to fatigue and human error.

Recently, medical professionals have begun to use Computer Aided Diagnostic (CAD) tools to assist them in
20 detecting suspicious features. Experiments have shown that the performance of radiologists improves when they are assisted by detection software that marks suspicious areas. See Brake and Karssemeijer, "Detection of Stellate Breast Abnormalities," Digital Mammography pp. 341-346 (Elsevier
25 Science 1996), the contents of which are hereby incorporated by reference into the present disclosure.

FIG. 1 shows a continuum of lesions that may appear in mammograms, ranging from a pure mass or pure density lesion on the left to a spiculated lesion on the right. Other
30 types of lesions include architectural distortions, which have radiating lines similar to spiculated lesions but are generally without a central mass, and radial scars, which appear as criss-crossed lines and also are generally without a central mass.

35 Sharply defined masses such as those shown at the left in FIG. 1 are rarely associated with malignant tumors, while spiculated masses can be a strong indication of malignancy.

Lesions having the characteristics of architectural distortions or radial scars may also be cancerous, depending on their size and shape.

Accordingly, there is value in locating and analyzing
5 both the "mass" or "density" qualities and the
"spiculatedness" qualities of shapes found in digital
mammograms. CAD systems generally include "mass" (or
density) focused algorithms and "spiculation" focused
algorithms. Some algorithms attempt to use metrics of both
10 "massness" and "spiculatedness" to identify suspicious
portions of digital mammograms. Such algorithms are included
among the following references: Yin and Giger et. al.,
"Computerized Detection of Masses in Digital Mammograms:
Analysis of Bilateral Subtraction Images," Medical Physics,
15 Vol. 18, No. 5, pp. 955-963 (Sept./Oct. 1991); Sahiner et.
al., "Classification of Masses on Mammograms Using a Rubber-
Band Straightening Transform and Feature Analysis," Medical
Imaging, SPIE Symposium on Medical Imaging Paper No. 2710-06,
at p. 204 (1996); and Huo and Giger et al., "Analysis of
20 Spiculation in the Computerized Classification of
Mammographic Masses," Medical Physics, Vol. 22, No. 10, pp.
1569-1579 (Oct. 1995). The contents of the above references
are hereby incorporated by reference into the present
application.
25 Typical of the above algorithms, Huo and Giger take a
serial and dependent approach by first identifying masses and
subsequently identifying spiculatedness characteristics of
those masses. Huo and Giger demonstrate how the edges of
detected masses can be used to determine a measure of
30 spiculation -- i.e., spiculatedness. Huo and Giger, approach
the problem serially by first detecting the mass signature,
or density, in a mammogram, and then applying various
filtering analyses to filter out benign masses and false
detections, such as parenchymal structure. The Huo and Giger
35 approach initially depends on density, which is a feature
with low positive predictive value. It then attempts to
improve upon itself by measuring features with higher

positive predictive values, such as spiculation. The shortcomings of the Huo/Giger approach include the fact that the additional feature measurements typically depend on secondary algorithms that may be non-robust. These secondary
5 algorithms may include algorithms for spiculation, region growing, or segmentation of the mass boundaries. Also, these algorithms may display poor sensitivity on architectural distortions and radial scars which have no central density. Finally, because the algorithm is inherently serial, wherein
10 the spiculation information is computed after the mass information, the time for completion of the algorithm is the sum of the time for completion of the mass detection algorithm plus the spiculation detection algorithm, which can lead to disadvantageously slow results.

15 A direct "backward direction" algorithm for of spiculation detection is disclosed in Karssemeijer, "Recognition of Stellate Lesions in Digital Mammograms," Digital Mammography: Proceedings of the 2nd International Workshop on Digital Mammography, York, England, 10-12 July,
20 1994, pp. 211-219 (Elsevier Science 1994), the contents of which are hereby incorporated by reference into the present application. By "backward direction" it is meant that a "candidate point" is incrementally moved across the image by a distance corresponding to the desired resolution of the
25 spiculation search. At each candidate point, a set of "window computations" for a window of pixels surrounding the candidate point is performed, and a metric corresponding to the presence and/or strength of a spiculation centered on the candidate point is computed.

30 "Backward direction" algorithms are computationally intensive. For an image size of $N \times N$ pixels, there generally need to be on the order of $K(bN)^2$ computations, where K is the number of window computations for each candidate point and b is the reciprocal of the number of
35 image pixels between each candidate point. Because the number K is often proportional to the square or cube of the window size, the computational intensity of "backward

direction" approaches can easily become unwieldy. Another example of a "backward direction" spiculation algorithm is described in Kegelmeyer, "Computer-aided Mammographic Screening for Spiculated Lesions," Radiology, Vol. 191, pp. 5 331-337 (1994), the contents of which are hereby incorporated by reference into the present application. The computational complexity of "backward direction" spiculation algorithms may cause a CAD program to be too slow for practical use by medical professionals, such as radiologists. 10 Additionally, a practical implementation of a CAD system using a backward direction algorithm for spiculation detection would lead to inevitable dependency between the mass and spiculation algorithms. This is because, due to its slowness, the spiculation algorithm could only be applied to 15 a subset of interesting regions of the digital mammogram image, the interesting regions being pointed out by the presence of masses from the mass detection algorithm.

Accordingly, it would be desirable to provide a computer-assisted diagnosis (CAD) system for assisting in the 20 detection of suspicious lesions in medical images that has increased speed in computing the necessary mass information and spiculation information.

It would be further desirable to provide a computer-assisted diagnosis (CAD) system that has greater reliability 25 in detecting suspicious lesions of a digital mammogram that have characteristics similar to those of architectural distortions, radial scars, and spiculated lesions having very small central masses.

30

35

SUMMARY OF THE INVENTION

These and other objects of the present invention are achieved by an improved CAD system that incorporates
5 independent measurements of mass and spiculation characteristics as taken from a digital mammogram image. In a preferred embodiment, a forward spiculation detection algorithm is incorporated that is executed separately from a mass detection algorithm, and that is not dependent on any
10 results from the mass detection algorithm. The step of computing spiculation information may be performed before, during, or after the step of computing mass information, but in a preferred embodiment is performed concurrently in time with the mass detection algorithm for optimal time
15 performance of the overall system.

According to a preferred embodiment, after the mass information and spiculation information is determined, a classifier algorithm classifies locations in the digital mammogram according to their feature vectors, which comprise
20 the computed mass information and spiculation information. The classifier algorithm may incorporate any of a variety of classification algorithms known in the art, including linear classifier algorithms, quadratic classifier algorithms, K-nearest-neighbor classifier algorithms, decision tree
25 classifier algorithms, or neural network classifier algorithms. By way of non-limiting example, the classifier algorithm may classify locations into a two-category system including a "suspicious" category and a "normal" category.

30

35

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features and advantages of the present invention will be more readily apparent from the following detailed description of the invention in which:

5 FIG. 1 shows various types of lesions arranged in an order from pure mass to highly spiculated mass;

FIG. 2A is an outside view of an illustrative computer aided diagnostic (CAD) system;

FIG. 2B is a block diagram of an illustrative CAD
10 processing unit for use in the CAD system of FIG. 2A;

FIG. 3 is a flowchart showing steps taken by a CAD system in accordance with a preferred embodiment;

FIG. 4 is a flowchart showing further steps taken by a CAD system in accordance with a preferred embodiment.

15

DETAILED DESCRIPTION OF THE INVENTION

FIG. 2A is an outside view of an illustrative computer aided diagnostic (CAD) system 100 for assisting in the identification of suspicious areas in mammograms according to
20 the preferred embodiment. CAD system 100 comprises a CAD processing unit 102 and a viewing station 104. In general, CAD processing unit 102 scans a developed x-ray mammogram 101 into a digital mammogram image, processes the image, and outputs a highlighted digital mammogram for viewing at
25 viewing station 104.

FIG. 2B is a block diagram of CAD processing unit 102. In accordance with the invention, processing unit 102 is capable of performing a multiplicity of image processing algorithms designed to detect abnormalities such as
30 spiculation detection, mass detection, linear weighted comparisons and general mathematical comparisons, either serially or in parallel with the disclosed abnormality detection algorithms. Preferably, CAD processing unit 102 includes a digitizer 103, a central control unit 105, a
35 memory 108, a parallel processing unit 110, and I/O unit 112. Digitizer 103 illustratively is a scanner with 50 micron resolution.

Viewing station 104 is for conveniently viewing both the x-ray mammogram 101 on a backlighting station 120 and the output of the CAD processing unit 102 on a display device 118. The display device 118 may be, for example, a CRT
5 screen. The display device 118 typically shows a highlighted digital mammogram corresponding to the x-ray mammogram 101, the highlighted digital mammogram having information directing the attention of the radiologist to suspicious areas which may contain spiculation as determined by image
10 processing steps performed by the CAD processing unit 102. In one embodiment of the invention, the highlighted digital mammogram will have black or red circles circumscribing locations with suspected abnormalities. Since the x-ray mammogram 101 on backlighting station 120 and the digitized
15 mammogram on display device 118 are physically adjacent one another, one application of viewing station 104 is to use the digitized mammogram to direct the attention of the radiologist to the spiculated portions of the actual x-ray mammogram 101 itself.

20 It is to be appreciated that the CAD processing unit 102 is capable of performing other image processing algorithms on the digital mammogram in addition to or in parallel with the algorithms for detecting abnormalities in accordance with the preferred embodiment. In this manner, the radiologist may be
25 informed of several suspicious areas of the mammogram at once by viewing the display device 118, spiculation being one special type of suspicious area.

After the x-ray mammogram 101 passes through the CAD system 100, it undergoes processing similar to that currently
30 practiced in clinics. In addition, memory 108 of CAD processing unit 102 may be used in conjunction with I/O unit 112 to generate a permanent record of the highlighted digital mammogram described above, and/or may also be used to allow non-real-time viewing of the highlighted digital mammogram.

35 FIG. 3 is an overview showing steps performed by CAD processing unit 102 on the x-ray mammogram in accordance with a preferred embodiment. At step 302, the x-ray mammogram is

scanned in and digitized into a digital mammogram. The digital mammogram may be, for example, a 3000 x 4000 array of 12-bit gray scale pixel values. Such a digital mammogram would generally correspond to a typical 8" x 10" x-ray mammogram which has been digitized at a 50 micron spatial resolution. Because a full resolution image such as the 3000 x 4000 image described above is not necessary for the effectiveness of the preferred embodiment, the image may be locally averaged, using steps known in the art, down to a smaller size corresponding, for example, to a 200 micron spatial resolution. At such a resolution, a typical image would then be an M x N array of 12-bit gray scale pixel values, with M being near 900, for example, and N being near 1200, for example. In general, however, either the full resolution image or the locally averaged image may be used as the original digital mammogram in accordance with the preferred embodiment.

At step 304, a spiculation detection algorithm is performed on the digital mammogram. At step 306 a mass detection algorithm is run on the digital mammogram. In a preferred embodiment, steps 304 and 306 are carried out concurrently so as to optimize overall speed of the detection process. Also in a preferred embodiment, steps 304 and 306 are carried out independently, in that there is no data dependence between them. According to a preferred embodiment, the spiculation detection step 304 does not require any final or intermediate outputs from the mass detection step 306, and the mass detection step 306 does not require any final or intermediate outputs from the spiculation detection step 304. In addition to introducing the ability to make the overall algorithm faster, the independence of the mass detection and spiculation detection steps allows for increased detection of features characteristic of architectural distortions, radial scars, and in general otherwise suspicious lesions that do not have a significant central mass that is detected by the mass detection algorithm.

At step 308, a classifier algorithm is performed on feature vectors corresponding to locations in the digital mammogram. Each location in the digital mammogram has a corresponding feature vector, which can be defined as a set of characteristics, including the "massness" metrics and "spiculatedness" metrics that were determined previously at steps 304 and 306. A classifier is an algorithm or system that labels a feature vector as belonging to a specific class, such as "suspicious/normal," "malignant/benign," etc. Several types of classifiers exist in the art, including linear classifiers, quadratic classifiers, k-nearest-neighbor method classifiers, decision trees, and neural networks. As known in the art, classifiers are constructed using a data set of example vectors representing each class, called a training set or learning set. See generally Brake & Karssemeijer, *supra*, and references cited therein. Finally, at step 312, the digital mammogram image and a list of suspicious lesions are sent to the viewing station 104 for display.

Many spiculation detection algorithms are known in the art. Any number of these spiculation detection algorithms may be used to accomplish step 304. For example, step 304 may be satisfied by running either a backward or a forward spiculation detection algorithm. However, backward spiculation detection algorithms consume substantially more time, computer memory, and general resources than forward spiculation detection algorithms. For this reason, a preferred embodiment uses a forward spiculation detection algorithm. The information resulting from a spiculation detection algorithm may include such details as the geometrical coordinates of mammographic areas likely to contain spiculations, the size of the spiculation, or the like.

In step 306 of FIG. 3, a mass detection algorithm is run against the digitized mammogram. Importantly, step 306 is independent of step 304 in that the mass detection algorithm is run against the digitized mammogram without reference to

the spiculation detection algorithm of step 304, or the results of the spiculation detection algorithm of step 304. The independent nature of steps 304 and 306 is important because it solves the problem of that prior art in which a
5 mass detection algorithm and a spiculation detection algorithm are serially applied. In the prior art, a mass detection algorithm is applied to the digitized image first so that areas with "density," or mass, can be identified. In this way, a mass detection algorithm making a "first cut"
10 singles out only areas that may contain suspicious masses. Next, a spiculation detection algorithm is applied only to those suspicious areas that may contain masses, rather than to the entire mammographic image. Thus, spiculated masses with low density may be overlooked.

15 The preferred embodiment solves the "first cut" problem of the prior art because both a spiculation detection algorithm, step 304, and a mass detection algorithm, step 306, are independently applied to the entire mammographic image. By applying both a spiculation detection algorithm
20 and a mass detection algorithm to the entire image, an increased number of suspicious areas are likely to be identified. For example, areas containing low density spiculated masses may be identified. Step 306 can be executed using any number of mass detection algorithms known
25 in the art.

FIG. 4 shows exemplary steps corresponding to the classification step 308 when a simple linear classifier method is used. The example of FIG. 4 is presented for clarity and completeness of disclosure, to allow the reader
30 to more fully comprehend the context of the preferred embodiment, and is not intended to limit the scope of the present invention. It is to be understood that any of a variety of classifiers can be used at step 308, each having certain advantages, disadvantages, and tradeoffs in terms of
35 training time, computation time, probability of false positives, probability of missed detection, and other factors. The method described herein has an advantage,

however, of simplicity and speed of training and computation time.

The classification method of FIG. 4 supposes the common result that the spiculation detection algorithm and the mass
5 detection algorithm produce a scalar spiculation metric f_s and a scalar mass metric f_m , respectively, each having a value normalized between 0 and 100, for example. Thus, for example, a given location may have a scalar spiculation
10 metric f_s of 90, which would indicate a very high degree of spiculatedness, and a scalar mass metric f_m of 5, which would indicate a very faint or small mass. In this simple case, the pair (f_s, f_m) forms the feature vector at each location.

At step 402, the scalar spiculation metric f_s and the scalar mass metric f_m are each multiplied by weighting factors
15 a_s and a_m , respectively, and the weighted factors are added to form a result. At step 404, the result from step 402 is compared to a predetermined threshold C. If the result from step 402 is greater than the predetermined threshold C, the location is identified as "suspicious" at step 406.
20 Otherwise, the location is identified as "normal" at step 408. The choices for a_s , a_m , and C define the parameters for the linear classifier algorithm of FIG. 4. Using methods known in the art, these linear classifier parameters are statistically preselected using a large training set of
25 feature vectors that are known to represent each class being identified.

As known in the art, the parameters of the classifier may be changed to achieve different levels of utility and results. Even in the simple linear classifier example of
30 FIG. 4, it is readily observed that the predetermined threshold C may be lowered to increase system sensitivity and bring more mammograms to the attention of the radiologist. This would, of course, have the negative impact of increasing the overall number of mammograms and false positives that the
35 radiologist must analyze. Conversely, the predetermined threshold C may be increased to decrease system sensitivity, and would have the converse result of necessitating less

radiologist intervention while risking more missed diagnoses.

The linear classifier technique of FIG. 4 can be generalized and extended to include several feature vector metrics (f_1, f_2, f_3, \dots) and several weights ($a_1, a_2, a_3 \dots$). Other feature vector metrics may include, for example, the "sphericity" and "eccentricity" metrics disclosed in the parent U.S. App. No. 09/103,290, *supra*.

It is also within the scope of the preferred embodiments to for the classifier to identify more than two classes. For example, a classifier may be constructed to form four sets -- "suspicious -- more spiculated"; "suspicious -- more density;" "suspicious -- similar density and spiculation", and "normal." One use of the multiple classes would be, for example, to place red triangles around "suspicious -- more density" locations on the CRT display 118, placing blue triangles around "suspicious - more spiculation" locations, and green squares around "suspicious -- similar density and spiculation" locations. In this manner, the radiologist would be made aware of different types of suspicious lesions in different ways.

An alternative embodiment uses a look up table to combine the independent information at each location in the digitized mammogram. The look up table might be a two dimensional matrix that indicates for numerical values of mass information on a first axis and spiculation information on a second axis whether the combination of mass information and spiculation information is suspicious.

Both linear classifiers and neural networks are types of classifiers. In order to be able to use a classifier, prior statistical knowledge about the digital mammograms is necessary. For example, see Brake and Karssemeijer, "Detection of Stellate Breast Abnormalities," Digital Mammography pp. 341-346 (Elsevier Science 1996). Other types of classifiers include the Bayes optimal classifier, quadratic classifiers, the k th-nearest neighbor classifier, and artificial neural networks, or the like. One skilled in

the art will know that any of these pattern classification systems could be used according to the preferred embodiments.

Once an abnormality is located, the preferred embodiment could be extended to advantageously create further

5 classification parameters to indicate areas according to probable seriousness or likelihood of locating a benign abnormality versus locating a malignant abnormality. Such a further classification step could assist the medical professional in decision making and prioritization.

10 Although preferred embodiments have been described with respect to a CAD system for detecting suspicious lesions in digital mammograms, those skilled in the art should be able to apply the preferred embodiments to any number of other computer aided diagnosis systems.

15

20

25

30

35

CLAIMS

What is claimed is:

1. A method for automated detection of suspicious lesions
5 in a digital mammogram, comprising the steps of:

computing mass information corresponding to the
digital mammogram, said mass information having mass
location information;

- 10 independent of said step of computing mass
information, computing spiculation information
corresponding to the digital mammogram, said spiculation
information having spiculation location information; and

- 15 identifying suspicious lesions in the digital
mammogram using said mass information and said
spiculation information.

2. The method of claim 1, wherein said step of computing
spiculation information is performed prior to or concurrently
with said step of computing mass information.

- 20 3. The method of claim 2, wherein said spiculation
information is computed from a set of information other than
said mass information, for allowing faster and more reliable
detection of suspicious lesions in the digital mammogram.

- 25 4. The method of claim 3, wherein said step of identifying
suspicious lesions includes the step of using a classifier
algorithm to classify a feature vector corresponding to at
least one location in said digital mammogram, each feature
30 vector comprising that portion of said mass information and
said spiculation information that corresponds to that
location.

5. The method of claim 4, wherein said classifier algorithm
35 is used to classify feature vectors associated with each
location in said digital mammogram.

6. The method of claim 4, wherein said classifier algorithm comprises a linear classifier algorithm.

7. The method of claim 4, wherein said classifier comprises
5 a quadratic classifier algorithm.

8. The method of claim 6, said mass information comprising a mass metric, said spiculation information comprising a spiculation metric, said mass metric and said spiculation
10 metric being scalar quantities, said linear classifier algorithm comprising the steps of:

weighting said mass metric by a first weight to produce a weighted mass metric;

weighting said spiculation metric by a second
15 weight to produce a weighted spiculation metric;

combining said weighted mass metric and said weighted spiculation metric to produce a result;

comparing said result to a predetermined threshold;

identifying the corresponding location as
20 suspicious if said result is greater than said predetermined threshold;

and

identifying the corresponding location as normal if
said result is not greater than said predetermined
25 threshold.

9. The method of claim 8, wherein said first weight, said second weight, and said predetermined threshold are determined using a training algorithm on a training set of digital mammograms, said training set comprising a plurality
30 of examples of suspicious lesions and a plurality of examples of normal breast structure.

10. A computer program product for directing a computing apparatus to automatically detect suspicious lesions in a
35 digital mammogram, thus permitting the suspicious lesions to be brought to the attention of a medical professional, said computer program product comprising:

computer code for computing mass information
corresponding to the digital mammogram, said mass
information having mass location information;

5 computer code for computing, independent of the
computation of said mass information, spiculation
information corresponding to the digital mammogram, said
spiculation information having spiculation location
information; and

10 computer code for identifying suspicious lesions in
the digital mammogram using said mass information and
said spiculation information.

11. The computer program product of claim 10, wherein said
spiculation information is computed prior to or concurrently
15 with said step of computing mass information.

12. The computer program product of claim 11, wherein said
computer code for identifying suspicious lesions includes
computer code for using a classifier algorithm to classify a
20 feature vector corresponding to at least one location in said
digital mammogram, each feature vector comprising that
portion of said mass information and said spiculation
information that corresponds to that location.

25 13. The computer program product of claim 12, wherein said
classifier algorithm is used to classify feature vectors
associated with each location in said digital mammogram.

14. The computer program product of claim 13, said mass
30 information comprising a mass metric, said spiculation
information comprising a spiculation metric, said mass metric
and said spiculation metric being scalar quantities, said
linear classifier algorithm comprising the steps of:

weighting said mass metric by a first weight to
35 produce a weighted mass metric;

weighting said spiculation metric by a second
weight to produce a weighted spiculation metric;

combining said weighted mass metric and said
weighted spiculation metric to produce a result;
comparing said result to a predetermined threshold;
identifying the corresponding location as
5 suspicious if said result is greater than said
predetermined threshold;
and
identifying the corresponding location as normal if
said result is not greater than said predetermined
10 threshold.

15. An automated system for detecting suspicious
portions of a digitized mammogram, comprising:
means for computing mass information corresponding
15 to the digitized mammogram, said mass information having
mass location information;
means for computing spiculation information
corresponding to the digitized mammogram independent of
said mass information, said spiculation information
20 having spiculation location information; and
means for classifying said mass information and
said spiculation information for detecting the
suspicious portions of the digital mammogram.

25 16. The automated system of claim 15, wherein said means for
computing spiculation information computes said spiculation
information prior to or substantially in parallel with a
period in which said means for computing mass information
computes said mass information.

30 17. The automated system of claim 16, wherein said means for
computing spiculation information computes said spiculation
information using data other than said mass information.

35 18. The automated system of claim 17, wherein said means for
classifying comprises:

means for computing at least one combined
classification parameter defined by a combination of said
mass information and said spiculation information; and

means for identifying values for which said at
5 least one combined classification parameter corresponds to a
suspicious portion of the digital mammogram.

19. The automated system of claim 17, wherein said means for
classifying comprises means for implementing a neural network
10 algorithm capable of identifying the suspicious portions of
the digital mammogram using said mass information and said
spiculation information.

20. The automated system of claim 18, wherein said means for
15 classifying includes a look up table that is indexed
according to scalar quantities associated with said mass
information and said spiculation information.

20

25

30

35

ABSTRACT


A method and system for detecting suspicious portions of digital mammograms by using independently calculated mass and spiculation information is disclosed. The method is for use
5 in a computer aided diagnosis system that is designed to bring suspicious or possibly cancerous lesions in fibrous breast tissue to the attention of a radiologist or other medical professional. In a preferred embodiment, spiculation information and mass information are independently
10 calculated, with the computed spiculation information not being dependent on results of the mass information computation, thus leading to greater reliability. Systems according to a preferred embodiment also compute spiculation information either prior to, or concurrently with, the
15 computation of mass information, thus allowing increased overall system speed.

20

25

30

35



Prior Art

FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4

**DECLARATION
AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below at 201 et seq. underneath my name.

I believe I am the original, first and sole inventor if only one name is listed at 201 below, or an original, first and joint inventor if plural names are listed at 201 et seq. below, of the subject matter which is claimed and for which a patent is sought on the invention entitled

**METHOD AND SYSTEM FOR DETECTION OF SUSPICIOUS LESIONS IN DIGITAL MAMMOGRAMS USING A
COMBINATION OF SPICULATION AND DENSITY SIGNALS**

and for which a patent application:

☒ is attached hereto and includes amendment(s) filed on _____ (if applicable)

☐ was filed in the United States on _____ as Application No. _____ (for declaration not accompanying application)

with amendment(s) filed on _____ (if applicable)

☐ was filed as PCT international Application No. _____ on _____ and was amended under PCT Article 19 on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified application, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

EARLIEST FOREIGN APPLICATION(S), IF ANY, FILED PRIOR TO THE FILING DATE OF THE APPLICATION			
APPLICATION NUMBER	COUNTRY	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
			YES <input type="checkbox"/> NO <input type="checkbox"/>
			YES <input type="checkbox"/> NO <input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

APPLICATION NUMBER	FILING DATE

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NO.	FILING DATE	STATUS		
		PATENTED	PENDING	ABANDONED
09/103,290	6/23/98		X	
08/676,660	7/10/96		X	

POWER OF ATTORNEY: As a named inventor, I hereby appoint S. Leslie Misrock (Reg. No. 18872), Harry C. Jones, III (Reg. No. 20280), Berj A. Terzian (Reg. No. 20060), Gerald J. Flintoft (Reg. No. 20823), David Weild, III (Reg. No. 21094), Jonathan A. Marshall (Reg. No. 24614), Barry D. Rein (Reg. No. 22411), Stanton T. Lawrence, III (Reg. No. 25736), Isaac Jarkovsky (Reg. No. 22713), Joseph V. Colaianni (Reg. No. 20019), Charles E. McKenney (Reg. No. 22795), Philip T. Shannon (Reg. No. 24278), Francis E. Morris (Reg. No. 24615), Charles E. Miller (Reg. No. 24576), Gidon D. Stern (Reg. No. 27469), John J. Lauter, Jr. (Reg. No. 27814), Brian M. Poissant (Reg. No. 28462), Brian D. Coggio (Reg. No. 27624), Rory J. Radding (Reg. No. 28749), Stephen J. Harbulak (Reg. No. 29166), Donald J. Goodell (Reg. No. 19766), James N. Palik (Reg. No. 25510), Thomas E. Friebe (Reg. No. 29258), Laura A. Coruzzi (Reg. No. 30742), Jennifer Gordon (Reg. No. 30753), Jon R. Stark (Reg. No. 30111), Allan A. Fanucci (Reg. No. 30256), Geraldine F. Baldwin (Reg. No. 31232), Victor N. Balancia (Reg. No. 31231), Samuel B. Abrams (Reg. No. 30605), Steven I. Wallach (Reg. No. 35402), Marcia H. Sundeen (Reg. No. 30893), Paul J. Zegger (Reg. No. 33821), Edmond R. Bannon (Reg. No. 32110), Bruce J. Barker (Reg. No. 33291), Adriane M. Antler (Reg. No. 32605), Thomas G. Rowan (Reg. No. 34419), James G. Markey (Reg. No. 31636), Thomas D. Kohler (Reg. No. 32797), Scott D. Stimpson (Reg. No. 33607), Ann L. Gisolfi (Reg. No. 31956), and Mark A. Farley (Reg. No. 33170), all of Pennie & Edmonds LLP, whose addresses are 1155 Avenue of the Americas, New York, New York 10036, 1667 K Street N.W., Washington, DC 20006 and 3300 Hillview Avenue, Palo Alto, CA 94304, and each of them, my attorneys, to prosecute this application, and to transact all business in the Patent and Trademark Office connected therewith.

SEND CORRESPONDENCE TO: PENNIE & EDMONDS LLP 1155 AVENUE OF THE AMERICAS NEW YORK, N.Y. 10036-2711				DIRECT TELEPHONE CALLS TO: PENNIE & EDMONDS LLP DOCKETING (212) 790-2803	
201	FULL NAME OF INVENTOR	LAST NAME Roehrig	FIRST NAME Jimmy	MIDDLE NAME R.	
	RESIDENCE & CITIZENSHIP	CITY Palo Alto	STATE OR FOREIGN COUNTRY CA	COUNTRY OF CITIZENSHIP United States	
	POST OFFICE ADDRESS	STREET 28 Roosevelt Cittle	CITY Palo Alto	STATE OR COUNTRY CA	ZIP CODE 94306
202	FULL NAME OF INVENTOR	LAST NAME Doi	FIRST NAME Takeshi	MIDDLE NAME	
	RESIDENCE & CITIZENSHIP	CITY Palo Alto	STATE OR FOREIGN COUNTRY CA	COUNTRY OF CITIZENSHIP United States	
	POST OFFICE ADDRESS	STREET 3358 Bryant St.	CITY Palo Alto	STATE OR COUNTRY CA	ZIP CODE 94306
203	FULL NAME OF INVENTOR	LAST NAME Karssemeijer	FIRST NAME Nico	MIDDLE NAME	
	RESIDENCE & CITIZENSHIP	CITY Beek	STATE OR FOREIGN COUNTRY The Netherlands	COUNTRY OF CITIZENSHIP The Netherlands	
	POST OFFICE ADDRESS	STREET De Ruvenberg 14	CITY Beek	STATE OR COUNTRY The Netherlands	ZIP CODE 6573 DZ
204	FULL NAME OF INVENTOR	LAST NAME Te Brake	FIRST NAME Guido	MIDDLE NAME M.	
	RESIDENCE & CITIZENSHIP	CITY Utrecht	STATE OR FOREIGN COUNTRY The Netherlands	COUNTRY OF CITIZENSHIP The Netherlands	
	POST OFFICE ADDRESS	STREET L. Napoleonplantsoen 48 III	CITY Utrecht	STATE OR COUNTRY The Netherlands	ZIP CODE 3582 TS
205	FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME	
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
	POST OFFICE ADDRESS	STREET	CITY	STATE OR COUNTRY	ZIP CODE
206	FULL NAME OF INVENTOR	LAST NAME	FIRST NAME	MIDDLE NAME	
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
	POST OFFICE ADDRESS	STREET	CITY	STATE OR COUNTRY	ZIP CODE

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201 Jimmy R. Roehrig	SIGNATURE OF INVENTOR 202 Takeshi Doi	SIGNATURE OF INVENTOR 203 Nico Karssemeijer
DATE	DATE	DATE
SIGNATURE OF INVENTOR 204 Guido M. Te Brake	SIGNATURE OF INVENTOR 205	SIGNATURE OF INVENTOR 206
DATE	DATE	DATE